

HANDLES & METERS: OIL

CV11 Non-Metered Handles



363 117

CV11 Non-metered Dispense Valve

11 gpm max delivery

SAMSON control valves are used at the end of hose assembly to dispense lubricants and antifreeze solutions.

Safety trigger latch

Prevents accidental dispense

Locking trigger

For hands free operation

Aluminum die-cast body with ergonomic design

Stands the toughest environments and provides better comfort of operation

Large inlet screen filter

Keeping fluid clean with no flow restriction

Large inlet port swivel

Ball bearing design for maximum ease of use



363 118



363 116



363 114

TECHNICAL SPECIFICATIONS

Maximum flow rate	11 gal/min (40 l/min)
Maximum working pressure	1,450 psi (100 bar)
Fluid inlet	1/2" NPT (F)
Fluid outlet	1/2" NPT (F)
Wetted parts	Aluminum / Zinc plated steel / NBR
Fluid compatibility	Lubricants, ATF, antifreeze and antifreeze solutions
Weight (with no outlet)	1 lb (470 g)
Manual	836 854

MARKETS SERVED

- Car and truck dealerships
- Fast lube and maintenance shops
- Fleet service
- Mining and construction
- Lube trucks

FLUIDS HANDLED

- Synthetic and mineral based oil
- Hydraulic oil
- Gear lube
- Transmission fluid
- Antifreeze solutions

ORDER INFORMATION

Part No.	Description	Outlet part No.
363 100	Oil valve with no outlet	-
363 116	Oil valve with 60° rigid outlet and quarter turn non-drip tip	369 231
363 114	Oil valve with flexible outlet with 90° tube and quarter turn non-drip tip	369 227
363 117	Oil valve with formable outlet and quarter turn non-drip tip	369 233
363 118	Oil valve with formable outlet and quarter turn narrow non-drip tip	369 240

Non-drip tips are manufactured in brass.

All models include inlet swivel with shroud and the outlet listed for each model.