



363 054



363 053

### CV24 Non-metered High Flow Dispense Valve

#### 24 gpm max delivery

SAMSON high flow delivery control valves are used at the end of hose assembly to dispense large volumes of lubricants and antifreeze solutions.

#### Safety trigger guard

Prevents accidental dispense

#### Locking trigger

For hands free operation

#### Heavy-Duty aluminum die-cast body with ergonomic design

Stands the toughest working conditions

#### Large inlet screen filter

Keeping fluid clean with no flow restriction

#### Large inlet port swivel

Ball bearing design for maximum use comfort

#### High flow pressure balanced valve

Maximum reliability and ease of use

### TECHNICAL SPECIFICATIONS

Maximum flow rate	24 gal/min (90 l/min)
Maximum working pressure	1,450 psi (100 bar)
Fluid inlet	3/4" NPT(F) or 1" NPT(F)
Fluid outlet	3/4" BSP (F)
Wetted parts	Aluminum / Zinc plated steel and brass / NBR
Fluid compatibility	All type of synthetic and mineral oils, antifreeze solutions, hydraulic fluid
Weight	4.5 lb (2.05 kg)
Manual	836 839

#### MARKETS SERVED

- Truck dealerships
- Maintenance shops
- Fleet service
- Mining and construction
- Lube trucks

#### FLUIDS HANDLED

- Synthetic and mineral based oil
- Hydraulic oil
- Gear lube
- Transmission fluid
- Antifreeze solutions

### ORDER INFORMATION

Part No.	Description	Outlet part No.
<b>363 053</b>	30° rigid with semiautomatic non-drip tip	3/4" NPT(F)
<b>363 054</b>	Flexible outlet with semiautomatic non-drip tip	3/4" NPT(F)
<b>363 055</b>	30° rigid with semiautomatic non-drip tip	1" NPT(F)
<b>363 056</b>	Flexible outlet with semiautomatic non-drip tip	1" NPT(F)