

Special Control Valves, Meters & Dispensers

Special Control valves are designed for use with pure antifreeze and water based solutions of antifreeze, windshield wash solutions, motor oils, gear oils & ATF.

Non-metered/Metered Control Valve Water Based Fluids

TECHNICAL SPECIFICATIONS



	186 300	365 575
Maximum flow rate	8 gal/min	
Accuracy	--	
Maximum working pressure	570 psi (39 bar)	435 psi (30 bar)
Fluid inlet	1/2" NPT(F)	
Fluid outlet	1/2" NPT(F)	
Wetted parts	Polyamide, brass stainless steel	Polyamide, brass stainless steel, PVC
Fluid compatibility	Windshield wash, antifreeze	Windshield wash, coolant, antifreeze
Manual	818 800	836 826

FLUIDS HANDLED

- Windshield wash
- Antifreeze solutions



ORDER INFORMATION

186 300	Special Fluids Non-Meter 1/2"
365 575	Special Fluids Meter 1/2"

Preset Digital Meters Lubricants

TECHNICAL SPECIFICATIONS

	2199	2199SF	365 300
Maximum flow rate	8 gal/min		
Maximum working pressure	1,000 psi (70 bar)	1,015 psi (70 bar)	
Fluid inlet	1/2" NPT(F)		
Fluid outlet	1/2" NPT(F)		
Wetted parts	Acetal, SS, Buna-N, PU		Acetal, SS, brass, Buna-N, PU
Fluid compatibility	Motor/gear oil, ATF, hydraulic fluid	Windshield wash, antifreeze	Motor/gear oil, ATF, antifreeze, hydraulic fluid
Manual	M00227	M00227	--

FLUIDS HANDLED

- Synthetic and mineral based oil
- Hydraulic oil
- Gear lube
- Antifreeze solutions

ORDER INFORMATION

2199	Preset Electronic Meter
2199SF	Preset Electronic Meter for Special Fluids
365 300	Preset Electronic Meter-Adjustable Rigid Outlet