

OIL HANDLE ACCESSORIES In-Line Meters

	366 000	Max Working Pressure GPM Fluid Inlet Fluid Outlet Accuracy Power Source Wetted Materials	1,450 psi (100 bar) up to 8 gal/min 1/2" NPT(F) 1/2" NPT(F) +/- .05% 2x "AAA" 1.5 Batteries Acetylal, Aluminum, Stainless Steel, NBR, Zinc Plated Steel, TPU, Polyamide, PVC
	366 060	Max Working Pressure GPM Fluid Inlet Fluid Outlet Accuracy Power Source Wetted Materials	1,450 psi (100 bar) up to 21 gal/min 1/2" NPT(F) 1/2" NPT(F) +/- .05% 2x "AAA" 1.5 Batteries Acetylal, Aluminum, Stainless Steel, NBR, Zinc Plated Steel, TPU, Polyamide, PVC
	366 010	Max Working Pressure GPM Fluid Inlet Fluid Outlet Accuracy Power Source Wetted Materials	1,450 psi (100 bar) up to 14 gal/min 1/2" BSPP(F) 1/2" BSPP(F) +/- .05% 2x "AAA" 1.5 Batteries Acetylal, Aluminum, Stainless Steel, NBR, Zinc Plated Steel, TPU, Polyamide, PVC
	366 020	Max Working Pressure GPM Fluid Inlet Fluid Outlet Accuracy Power Source Wetted Materials	1,450 psi (100 bar) up to 14 gal/min 1/2" NPT(F) 1/2" NPT(F) +/- .05% 2x "AAA" 1.5 Batteries AISI 316 Stainless steel, Vectra, Viton
	366 855	Oval Gear In-Line Meter - Liters	
	366 856	Oval Gear In-Line Meter - Quarts/Gallons	
		Max Working Pressure GPM Fluid Inlet Fluid Outlet Accuracy Wetted Materials	1,000 psi (70 bar) .26 to 7.1 gal/min (1-27 lpm) 1/2" NPT(F) 1/2" NPT(F) +/- 1% Acetylal, Aluminum, Stainless Steel, NBR, Zinc Plated Steel, TPU, Polyamide, PVC

GREASE HANDLE ACCESSORIES In-Line Meter - Oval

	411 103	Max Free Flow Rate Max Working Pressure Fluid Inlet Fluid Outlet Accuracy Power Source Wetted Materials	2.2 lb/min (1 Kg/min) 8,000 psi (552 bar) 1/8" NPT(F) 1/8" NPT(F) +/- 3.0% 2x "AAA" 1.5 Batteries Aluminum, Stainless Steel
--	----------------	---	---