

WASTE OIL DRAINS: GRAVITY UNITS



3723



3733



3724



3734

ORDER INFORMATION

Part no.	Description	Service manual
REMOTE PUMP DISCHARGE		
3733	18 gallon gravity waste oil drain	SM837815
3723	27 gallon gravity waste oil drain	SM837809
PRESSURE DISCHARGE		
3734	18 gallon gravity waste oil drain	SM837812
3724	27 gallon gravity waste oil drain	SM837805
Recommended Accessories		
737 968	Optional bowl extension	

Waste Fluid Handling

MARKETS SERVED

- Car and truck dealers
- Service shops
- Quick lubes

FLUIDS HANDLED

- Antifreeze solutions
- Synthetic and mineral oils
- Waste oil

Mobile waste oil drains are used for gravity or suction collection of motor oil and gear oil, as well as other automotive, non-aggressive A-III class fluids like antifreeze.

Once full, depending on model, the reservoir can be discharged either using a remote pump through a dry-break or a cam-lock connector or pressurizing the unit reservoir at 3.5 psi (0.5 bar) maximum.

All models include

5 gallon capacity, height adjustable collection bowl and a level gauge

Over-sized extension bowl

All 27 gallon models include over-sized extension bowl for wider reach with anti-splash screen.