ACCESSORIES: MEASURES, TANKS, VALVES



Measures & Funnels

4	2351	7 1/2" funnel with flex- spout, filter, anti-splash rim and finger grip
1	2352	Heavy-duty funnel with regular filter
	2353	Large heavy-duty funnel with diesel filter
	2377	5 qt. flex-spout, measure with lid quart & liter calibration
0	996 641	Flex spout for 2351 and 2377
	992 377	Lid for 2377

Tank Gauges swing arm style float - 2" tank opening



2640	Tanks with 32" interior height
2641	Tanks with 44" interior height
2642	Tanks with 48" interior height
2643	Tanks with 60" interior height
2644	Tanks with 72" interior height

High Level Tank Sensor

Air operated float level sensor alarm with high level sensor and alarm whistle, rotating collar allows 360° indexing of float



OA1	Overfill warning valve Valve is used to shut-off the air supply to the pump when the tank approaches full capacity. 6 1/2" shut-off height
OA1EXT	Overfill warning valve Valve is used to shut-off the air supply to the pump when the tank approaches full capacity. 17 3/8" shut-off height

Fill Caps & Tank Vents

	2631	2" Vented style Fill Cap with hinged cover
	2632	2" Standard (mushroom) Vent
	2633	3" Emergency Vent
	2634	3" Emergency Vent

LP Ball Valves (F X F) 400 psi



	-
2013	1/4" NPT
2088	1/2" NPT
2091	3/4" NPT
2084	1" NPT

MP Ball Valves (F X F) 2,000 psi

	2074	1/2" NPT
	2083	3/4" NPT
	2090	1" NPT
	2082	1 1/2" NPT

HP Needle Valve (F X F) 10,000 psi



,	- /
2077	1/2" NPT
2089	3/4" NPT
2093	1" NPT

164

www.samsoncorporation.com

Technical specifications are subject to change without prior notice